

S
O
U
S

V
I
D
E



Ideal for restaurants, caterers, central kitchens, liquid products...

- Auto-Vacuum process ensures that you get constant results no matter the size or quantity of products you are vacuum packaging.
- 40 or 63 m³/h Busch pump with high efficiency, reliable and robust oxygen evacuation up to 99.999% (at 2 mbars)
- Sealing bars: 2 x 26"
Distance between sealing bars: 17.5"
- Inside chamber dimension: 26.5" x 20.5" x 9.5"





Auto mode: always consistent and accurate

The Auto-vacuum mode performs a complete MAP or full vacuum packaging process smartly. Whatever is your product, the Hi-Tech Auto series machines adjust the running process entirely by itself to ensure that you get the result you



Programmable: the way you want

Memorizing up to 15 different programmable settings for your specialized products.




Autoclean: always optimal

Auto-cleaning process helps you keep your unit and pump at their optimized performance and extend their life.

Model 226

Spill liquid detection




Roomy chamber with 9.5 inch height and two (2) sealing bars.



Equipped with 40 or 63 m³/h, 230V, 3 phases, 60 Hz, 2 or 3 HP



Designed features



Vacuum package easily and without and spills large volume and amount of liquide products such as soups, sauces, stews, mash vegetables, pickled foods, etc.

- Busch pump with high efficiency, reliable and robust to ensure high vacuum level up to 2 mbars, and able to run long hours of non-stop production.
- Uniform and weld-sealing (tear resistant) with two (2) V-shape Ni-Cr wires RoSH compliant on each seal bar.
- Chamber is designed roomy to fit large cuts.
- Our dimensions are designed for maximum arrangements of various North American pouches size.
- Adjustable shims with easy set-up supports help you dispose and manipulate pouches fast and easy.
- Wide open dome lid facilitates fast loading and unloading of pouches.
- Unobstructed visual control of packaging process with whole see-through lid.

Tech Specs

Standard features

Options

Busch pump	40 m³/h, ultimate pressure of 2 mbar	63 m³/h
Electrical requirement	230 VAC, 3 phases, 60 Hz	220 V, 1 phase
Overall dimension	25.25" x 32.5" x 39.25" (lid closed)	
Inside chamber size	26" 1/2 x 20" 1/2 x 9" 1/4	
Length of seal bars	2 x 26"	Integrated bags cut-off in seal bar
Weight (approx.)	410 lbs	
Sealing element	two (2) Ni-Cr wires, RoHS compliant	Heavy duty sealing
Duty cycle	from 8 to 90 seconds	Customized for special applications
Chamber	Aluminum with white epoxy powder coating	High grade stainless steel
Working surface	Plastic HDPE shim for liquid products	
Ready for gas flush	Easy plug-in terminal ready on unit	Gas flush option kit



HI-TECH VACUUM inc., 1445A, RR5, Saint-Cyrille-de-Wendover, Quebec, J1Z 1S5 Canada
Tel.: (819) 397-4888 Fax: (819) 397-4644
Web: www.hitechvacuum.com email: info@hitechvacuum.com



Designed and made in Canada