

S
O
U
S
V
I
D
E



Highly suitable for restaurants, caterers, central kitchen ...

- 24 m³/h Busch pump with high efficiency, reliable and robust to ensure high vacuum level up to 2 mbars, and able to run long hours of non-stop production.
- Sealing bars: 2 x 19"
Distance between sealing bars: 14"
- Inside chamber dimension: 21.5" x 16.5" x 7.5"
- Ease and precision of operations with Classic and Expert modes.



Specifications

Model Tilt Nel 219NR



Classic mode: Quick and easy

Set easily and quickly your vacuum processes with peace of mind using the Classic Mode.



Expert mode: precise and subtle


Use the Expert mode to manually adjust the MAP process to fit your products and obtain the result to your finest detail.



One button for all functions

The push & turn button gives you access to more functions such as QuickSeal, QuickStop, Maintenance and more

Model 219



Front



Quick Seal


Roomy chamber with 7.25" height and two (2) sealing bars.



Equipped with 24 m³/h, 115V, 1 phase, 60 Hz, 1.25 HP



Designed features



Vacuum package easily and quickly large amount of liquid products such as soups, sauces, stew, mashed vegetables, marinated foods, etc.

- Busch pump with high efficiency, reliable and robust to ensure high vacuum level up to 2 mbars, and able to run long hours of non-stop production.
- Uniform and weld-sealing (tear resistant) with two (2) V-shape Ni-Cr wires RoSH compliant on each seal bar.
- Chamber is designed roomy to fit large cuts.
- Our dimensions are designed for maximum arrangements of various North American pouches size.
- Adjustable shims with easy set-up supports help you dispose and manipulate pouches fast and easy.
- Wide open dome lid facilitates fast loading and unloading of pouches.
- Unobstructed visual control of packaging process with whole see-through lid.

Tech Specs

Standard features

Option

| | | |
|------------------------|---|-------------------------------------|
| Busch pump | 24 m ³ /h, ultimate pressure of 2 mbar | |
| Electrical requirement | 120 VAC, 15 A, 1.25 HP | |
| Overall dimension | 26.5" x 23" x 55" (lid opened) | |
| Inside chamber size | 16" 3/4 x 19" 1/2 x 7" 1/4 | |
| Length of seal bars | 2 x 19" | Integrated bags cut-off in seal bar |
| Weight (approx.) | 255 lbs | |
| Sealing element | two (2) Ni-Cr wires, RoHS compliant | Heavy duty sealing |
| Duty cycle | from 8 to 90 seconds | Customized for special applications |
| Chamber | Aluminum with white epoxy powder coating | High grade stainless steel |
| Working surface | Plastic HDPE shims | |
| Ready for gas flush | Easy plug-in terminal ready on unit | Gas flush option kit |



Designed and made in Canada

HITECH VACUUM inc., 1445A, RR5, Saint-Cyrille-de-Wendover, Quebec, J1Z 1S5 Canada
 Tel.: (819) 397-4888 Fax: (819) 397-4644
 Web: www.hitechvacuum.com email: info@hitechvacuum.com